

AMENDMENT UNDER 37 CFR § 1.111  
Serial No. 10/057,896

**AMENDMENTS TO THE CLAIMS**

This listing of the claims replaces all prior versions, and listings, of claims in the application:

**LISTING OF CLAIMS**

1. [CURRENTLY AMENDED] A method of monitoring optical performance of a Dense Wave Division Multiplex (DWDM) optical communication system in which a plurality of channels are multiplexed within an optical fiber, the method comprising steps of:  
  
receiving an aggregate optical signal containing an optical data signal transported through a respective one of the channels, the optical data signal being a modulated by a respective predetermined spreading code;  
  
imposing a wavelength-dependent delay on the received aggregate optical signal;  
  
detecting a modulation power of the respective predetermined spreading code; and  
  
estimating an optical power of the optical data signal using the detected modulation power of the respective predetermined spreading code.
2. [ORIGINAL] A method as claimed in claim 1, wherein the predetermined spreading code is unique across all of the channels multiplexed within the fiber.
3. [ORIGINAL] A method as claimed in claim 2, wherein the predetermined spreading code comprises a spectrally white bit sequence having a predetermined chip duration.
4. [CANCELLED]
5. [CANCELLED]
6. [CANCELLED]

AMENDMENT UNDER 37 CFR § 1.111  
Serial No. 10/057,896

7. [CURRENTLY AMENDED] A method as claimed in claim 53, wherein a difference between the respective ~~predetermined time~~ delays of any two channels is equivalent to at least one spreading code chip duration.
8. [CURRENTLY AMENDED] A method as claimed in claim 1, wherein the step of detecting a modulation power of the predetermined spreading code comprises steps of:  
~~converting an the aggregate light beam optical signal composed of optical signals within all of the channels of the fiber,~~ into a corresponding electrical signal;  
decomposing the electrical signal into the predetermined spreading code of the optical signal; and  
measuring an amplitude of the decomposed electrical signal.
9. [ORIGINAL] A method as claimed in claim 8, wherein the step of decomposing the electrical signal comprises a step of multiplying the electrical signal by the predetermined spreading code.
10. [CURRENTLY AMENDED] A method as claimed in claim 1, wherein the aggregate optical signal is received as a ~~data~~ signal at a downstream end of the optical fiber, and the estimated optical power of the optical data signal is indicative of gain/attenuation experienced by the optical data signal within the fiber.
11. [CURRENTLY AMENDED] A method as claimed in claim 1, wherein the aggregate optical signal is received as a reflected signal at an upstream end of the optical fiber, and the estimated optical power of the optical data signal is indicative of a reflection of the optical data signal in an upstream direction of the fiber.
12. [ORIGINAL] A method as claimed in claim 11, further comprising a step of estimating a distance to a point of reflection.
13. [ORIGINAL] A method as claimed in claim 12, wherein the step of estimating the distance comprises steps of:

AMENDMENT UNDER 37 CFR § 1.111  
Serial No. 10/057,896

converting a reflected light beam within the fiber into a corresponding electrical signal;

multiplying the electrical signal by a plurality of copies of the spreading code, each copy having a respective different time delay;

auto-correlating each multiplication result to identify the time delay that most closely matches a time delay of the spreading code in the reflected light beam; and

estimating a distance to the point of reflection based on the identified time delay.

14. [CURRENTLY AMENDED] An optical performance monitor adapted for monitoring optical performance of a Dense Wave Division Multiplex (DWDM) optical communication system in which a plurality of channels are multiplexed within an optical fiber, the monitor comprising:

receiving means for receiving an aggregate optical signal containing an optical data signal transported through a respective one of the channels, the optical data signal being modulated by a respective predetermined spreading code;

an optical delay filter for imposing a wavelength-dependent delay on the received aggregate optical signal;

detecting means for detecting a modulation power of the respective predetermined spreading code; and

estimating means for estimating an optical power of the optical data signal using the detected modulation power of the respective predetermined spreading code.

15. [CANCELLED]

16. [CANCELLED]

17. [CANCELLED]

AMENDMENT UNDER 37 CFR § 1.111  
Serial No. 10/057,896

18. [CURRENTLY AMENDED] An optical performance monitor as claimed in claim 14, wherein a difference between the respective ~~predetermined~~ time delays of any two channels is equivalent to at least one spreading code chip duration.
19. [CURRENTLY AMENDED] An optical performance monitor as claimed in claim 14, wherein the detecting means is adapted to:  
~~convert an aggregate light beam optical signal composed of optical signals within all of the channels of the fiber,~~ into a corresponding electrical signal;  
decompose the electrical signal into the predetermined spreading code of the optical signal; and  
measure an amplitude of the decomposed electrical signal.
20. [ORIGINAL] An optical performance monitor as claimed in claim 19, wherein the detecting means is adapted to decompose the electrical signal by multiplying the electrical signal by the predetermined spreading code.
21. [CURRENTLY AMENDED] An optical performance monitor as claimed in claim 14, wherein:  
the receiving means is adapted to receive the aggregate optical signal as a ~~data~~ signal at a downstream end of the optical fiber; and  
the estimating means is adapted to estimate gain/attenuation experienced by the optical data signal within the fiber from the estimated optical power of the optical data signal.
22. [CURRENTLY AMENDED] An optical performance monitor as claimed in claim 14, wherein:  
the receiving means is adapted to receive the aggregate optical signal as a reflected signal at an upstream end of the optical fiber; and

AMENDMENT UNDER 37 CFR § 1.111  
Serial No. 10/057,896

the estimating means is adapted to estimate the reflection of the optical data signal in an upstream direction of the fiber, from the estimated optical power of the optical data signal.

23. [ORIGINAL] An optical performance monitor as claimed in claim 22, wherein the estimating means is further adapted to estimate a distance to a point of reflection.

24. [CURRENTLY AMENDED] An optical performance monitor as claimed in claim 23, wherein:

the receiving means is further adapted to convert ~~a-the reflected light beam-signal within the fiber~~ into a corresponding electrical signal;

the detecting means is further adapted to multiply the electrical signal by a plurality of copies of the spreading code, each copy having a respective different time delay; and

the estimating means is further adapted to:

auto-correlate each multiplication result to identify the time delay that most closely matches a time delay of the spreading code in the reflected light beam; and

estimate a distance to the point of reflection based on the identified time delay.